

CS-2050 Specifications

basic specifications:

Configuration:	Desktop Digital Multifunctional with Standard 300 x 2 Sheet Paper Drawers Plus 50 Sheet Multi-Purpose Tray, 64MB RAM for Scan Once Print Many and Electronic Sort, Standard Printing and Network Interface, Optional Network Scan and Fax, Optional 50 Sheet Document Processor, Duplex and Paper Handling.
Resolution:	600 x 600 DPI/ 256 Levels; Fast 1200 DPI: 2400 x 600 DPI w/KIR Print Resolution
Copier Memory:	Standard 64MB RAM upgradeable to 256MB via 100 Pin DIMMS (1 Slot)
Magnification:	Full Size, Auto Magnification, Plus 50-200% Zoom in 1% Increments
Electrical Requirements:	120V, 60Hz, 9.0A
Dimensions:	22.6"W x 23.3"D x 23.9"H
Weight:	120.0 lbs
Max Monthly Volume:	30,000 Pages per Month

output speeds:

Warm-Up Time:	Within 20 Seconds
First Copy Out:	5.9 Seconds
First Print Out:	5.5 Seconds
Pages Per Minute:	20 Letter, 11 Legal, 10 Ledger

paper supply:

Standard Paper Sources:	300 x 2 Sheet Drawers, 50 Sheet MPT
Drawer Paper Size:	5.5" x 8.5" - 11" x 17"
MPT Paper Size:	5.5" x 8.5" - 11" x 17"
Std / Max Paper Capacity:	650/ 1250
Paper Weight:	16-28 lb bond via Paper Drawers, 13 lb Bond -90 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Envelopes

copy functions:

Imaging Modes:	Auto, Text, Photo, Text / Photo, Manual, ECO
Continuous Copy:	Up to 999, Auto Reset to 1
Additional Features:	Auto Magnification and Paper Select, Scan Once Print Many, Electronic Sort, Rotate Sort, 2 in 1, 4 in 1, Border Erase, Margin Shift, ECO Mode, 100 Management Codes

paper handling options:

document processor: DP-410

Type:	Reversing Automatic Document Feeder
Acceptable Originals:	5.5" x 8.5" - 11" x 17"
Capacity:	50 Sheet RADF
Speed:	25 Originals per Minute
Paper Weight:	13 lb Bond - 90 lb Index
Dimensions/Weight:	21.7"H x 19.0"D x 4.7"H/ 13.2 lbs.

duplex: DU-410

Type:	Stackless
Paper Size:	5.5" x 8.5" - 11" x 17"
Paper Weight:	16 - 20 lb Bond
Duplex Modes:	1:2; 2:2; 2:1; Book:2/1

paper drawers: PF-410

Paper Capacity:	300 Sheets
Paper Weight:	16 - 28 lb Bond
Paper Size:	5.5" x 8.5" - 11" x 17"
Dimensions / Weight:	22.5"W x 21.2"D x 5.32"H / 15.4 lbs

internal finisher: DF-410

Stack Capacity:	500 Sheets
Paper Size:	5.5" x 8.5" - 11" x 17"
Paper Weight:	16 - 28 lb Bond
Staple Capacity:	30 Sheets: 8.5" x 11"; 20 Sheets 8.5" x 14", 11" x 17"
Dimensions / Weight:	12.2"W x 16.0"D x 6.3"H / 19.8 lbs

additional options:

Job Separator, Platen Cover, Copy Stand, 32MB Fax Memory

connectivity:

STANDARD PRINT:

Controller:	Embedded PowerPC750/ 300 MHz Controller
Printer Memory:	Standard 64MB, Upgradeable to 320MB via 100 Pin DIMMS, Optional MicroDrive, Standard CF Card Slot (Type 1)
Supported PDL/Emulations:	PRESCRIBE, PCL6 (PCL XL, PCL 5e), KPDL3 (PS3), KCGL (HP-GL/2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer
Fonts:	80 Outline Fonts for PCL XL/5e, 136 Outline Fonts for KPDL3, 17 Bitmap Fonts
Windows™ OS Compatibility:	Windows™ 95/98/Me/NT4.x/2000/XP/2003
Novell™ OS Compatibility:	Novell NetWare™ 3.x/4.x/5.x/6.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard 10/100BaseTX, Parallel IEEE1284, High Speed USB 2.0
KUJO LV Expansion Slots (1)	Optional IB-22 Enhanced Wireless NIC
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows™, PPD for Mac, PPD for Linux/UNIX, Certified UniDriver
Utilities:	KM-NET Viewer, KM-NET for Client, PDF Direct Print, KM-NET Printer Disk Manager, Kyocera Command Center, PRESCRIBE Utilities

SCAN: SCAN SYSTEM (F)

Resolution:	200, 300, 400, 600 DPI
Scan Speed:	Up to 20 Sheets Per Minute
File Formats:	PDF, TIFF
Connectivity:	NS-30 10/100BaseTX
Supported Protocols:	TCP/IP
Scanning Features:	Scan to PC/File, Scan to Mac, Scan to E-Mail, TWAIN
Driver:	TWAIN Driver
Utilities:	KM Scanner File Utility, Scan to Mac Utility, KM Scanner Address Book, Address Book Editor, Advanced Network Setup Utilities

FAX/NETWORK FAX: FAX SYSTEM (L)

Compatibility:	Super G3
Transmission Speed:	Approximately 2 Seconds per Page
Modem Speed:	33.6 Kbps w/ Auto Fallback
Data Compression:	JBIG, MMR, MR, MH
Fax Memory:	Std 8MB/ Max 40MB
Driver:	KM Network Fax Driver
Utilities:	Address Book for NW Fax, Address Editor for Fax
Additional Features:	Duplex TX/RX, Confidential TX/RX, Polling, Broadcasting, 2 in 1 RX



Specifications and design are subject to change without notice.
For the latest on connectivity visit www.copystar.com
All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters:
225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA
©2004 Kyocera Mita America, Inc.



www.copystar.com